YOUR IMPRESSION IS OUR SPECIALTY



Page 1/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.03.2023 Version number 1 Revision: 16.03.2023

1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: Cavex ScanSpray
- · **UFI**: GJ10-V0NP-000F-KV7Y
- · Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · **Application of the substance / the mixture** For dental purposes.
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Cavex Holland B.V.

Fustweg 5

2031 CJ Haarlem

The Netherlands

T +31 23 530 7700 E-Mail : dental@cavex.nl F +31 23 535 6482 Website : www.cavex.nl

- · Further information obtainable from: Product safety department
- · Emergency telephone number: During normal opening times: +31 23 530 7700

2 Hazards identification

- · Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS08 health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02 GHS07 GHS0

- · Signal word Danger
- · Hazard-determining components of labelling: pentane
- Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H332 Harmful if inhaled.

Printing date 16.03.2023 Version number 1 Revision: 16.03.2023

Trade name: Cavex ScanSpray

(Contd. of page 1)

H304 May be fatal if swallowed and enters airways. H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.
- · Dangerous components:

CAS: 109-66-0	pentane	7-15%
EINECS: 203-692-4	 ♦ Flam. Liq. 2, H225; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ STOT SE 3, H336, EUH066 	
CAS: 74-98-6	propane	2.5-10%
EINECS: 200-827-9	Flam. Gas 1A, H220; Press. Gas (Comp.), H280	
CAS: 75-28-5	isobutane	2.5-7.5%
EINECS: 200-857-2	Flam. Gas 1A, H220; Press. Gas (Comp.), H280	
CAS: 106-97-8	butane, pure	2.5-7.5%
EINECS: 203-448-7	Flam. Gas 1A, H220; Press. Gas (Comp.), H280	
CAS: 64-17-5	ethanol	≤2.5%
EINECS: 200-578-6	♦ Flam. Liq. 2, H225	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

Printing date 16.03.2023 Version number 1 Revision: 16.03.2023

Trade name: Cavex ScanSpray

(Contd. of page 2)

· Advice for firefighters

· Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: < 8 °Celsius.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Control parameters
- Ingredients with limit values that require monitoring at the workplace:

109-66-0 pentane

OEL Long-term value: 3000 mg/m³, 1000 ppm

IOELV

74-98-6 propane

OEL Asphx

75-28-5 isobutane

OEL Short-term value: 1000 ppm

106-97-8 butane, pure

OEL Short-term value: 1000 ppm

64-17-5 ethanol

OEL Short-term value: 1000 ppm

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 4)

Printing date 16.03.2023 Version number 1 Revision: 16.03.2023

Trade name: Cavex ScanSpray

(Contd. of page 3)

· Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection Not required.

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Odour threshold:
Melting point/freezing point:

Aerosol
White
Characteristic
Not determined.
Undetermined.

· Boiling point or initial boiling point and boiling

range 36 °C

· Flammability Not applicable.

· Lower and upper explosion limit

• **Lower:** 1.4 Vol % • **Upper:** 10.9 Vol %

· **Flash point:** Not applicable, as aerosol.

• Auto-ignition temperature: 285 °C

Decomposition temperature:pHNot determined.Not determined.

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

· Solubility

· water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value)
 Vapour pressure:
 Not determined.
 Not determined.

· Density and/or relative density

Density: Not determined.
Relative density Not determined.
Vapour density Not determined.

· Other information

· Appearance:

· Form: Aerosol

Important information on protection of health and environment, and on safety.

• **Ignition temperature:** Product is not selfigniting.

• Explosive properties: Not determined.

· Solvent content:

• Organic solvents: 33.0 % • VOC (EC) 40.00 %

· Change in condition

· Evaporation rate Not applicable.

(Contd. on page 5)

Printing date 16.03.2023 Version number 1 Revision: 16.03.2023

Trade name: Cavex ScanSpray

(Contd. of page 4)

· Information with regard to physical hazard classes

· Explosives Void · Flammable gases Void

· Aerosols Extremely flammable aerosol. Pressurised container:

May burst if heated.

· Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void **Pyrophoric solids** Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void Desensitised explosives Void

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Harmful if inhaled.
- · LD/LC50 values relevant for classification:

106-97-8 butane, pure

Inhalative LC50/4 h 658 mg/l (rat)

- · Primary irritant effect: -
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard May be fatal if swallowed and enters airways.
- · Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

12 Ecological information

- Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.

Printing date 16.03.2023 Version number 1 Revision: 16.03.2023

Trade name: Cavex ScanSpray

(Contd. of page 5)

- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · Other adverse effects
- · Remark: Harmful to fish
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN number or ID number

· ADR, IMDG, IATA UN1950

· UN proper shipping name

· ADR 1950 AEROSOLS AEROSOLS

· IATA AEROSOLS, flammable

- Transport hazard class(es)
- · ADR



· Class 2 5F Gases.

· Label 2.1

· IMDG, IATA



· Class 2.1 Gases.

· Label 2.1

· Packing group

ADR, IMDG, IATA not regulated
 Environmental hazards: Not applicable.
 Special precautions for user Not applicable.

· Hazard identification number (Kemler code):

· EMS Number: F-D,S-U

• Stowage Code SW1 Protected from sources of heat.

SW2 Clear of living quarters.

Segregation Code SG69 For AEROSOLS with a maximum capacity of 1

litre:

Printing date 16.03.2023 Version number 1 Revision: 16.03.2023

Trade name: Cavex ScanSpray

(Contd. of page 6)

Segregation as for class 9. Stow "separated from" class 1

except for division 1.4.

For AEROSOLS with a capacity above 1 litre:

Segregation as for the appropriate subdivision of class 2.

For WASTE AEROSOLS:

Segregation as for the appropriate subdivision of class 2.

· Maritime transport in bulk according to IMO

instruments Not applicable.

· Transport/Additional information:

· ADR

Limited quantities (LQ)Excepted quantities (EQ)Code: E0

Not permitted as Excepted Quantity

· Transport category 2 · Tunnel restriction code D

· IMDG

Limited quantities (LQ)Excepted quantities (EQ)Code: E0

Not permitted as Excepted Quantity

· UN "Model Regulation": UN 1950 AEROSOLS, 2.1

15 Regulatory information

- Directive 2004/42/EC
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

(Contd. of page 7)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.03.2023 Version number 1 Revision: 16.03.2023

Trade name: Cavex ScanSpray

Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Department issuing SDS: Product safety department

· Contact: .

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols – Category 1
Press. Gas (Comp.): Gases under pressure – Compressed gas
Flam. Liq. 2: Flammable liquids – Category 2
Acute Tox. 4: Acute toxicity – Category 4

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3